


TS16L – High voltage ceramic capacitors- Low D.F.

Use for coupling, and by pass circuit there are a stable and high reliability products.
 High voltage DC supplies or discharge (Lasers, X-ray apparatus, etc.).
 High frequency AC circuits.
 Noise suppressor or horizontal output circuits.



Specification

TEMP. CHARAC	Y5P (B)	Y5T
D. F. MAXIMUM	0.5%	0.1%
Working Voltage	1KV- 15KV	

T. C.	Y5P(B)	Y5T	DIMENSION			
			D	P	T	d
1KV	101~561	101~561	06	5	4	0.6
	102	102	07	5		
	202		10	7.5		
	332		14	10		
	472		16	10		
2KV	101~331	101~331	06	5	4	0.6
	391	471	07	5		
	561	681	08	5		
	102	102	10	7.5		
	152	152	12	7.5		
	222	222	14	10		
	302	302	16	10		
3KV		101~221	06	7.5	5	0.6
	221~331	331	07	7.5		
	471~561	471	08	7.5		
	681~821	821	10	7.5		
	102	102	12	7.5		

	152	152	14	10		
	222	202	16	10		
6.3KV		221	07	7.5	6	0.8
	221~331	331	08	7.5		
	471	471	10	7.5		
	102	102	13	10		
	152	152	16	10		
8KV		151	07	10	6	0.8
	221	221	08			
	391	391	10			
	681	681	13			
	102~122	122	16			
10KV		121	07	10	7	0.8
	101~221	181	09			
	331~471	331	11			
	561~681	561	14			
	102	102	17			
15KV		820	08	10	7	0.8
	101~221	151	10			
	331~471	331	13			
	561	561	16			