


TS16M – High voltage ceramic disc capacitors

Use for coupling and by pass circuit there are a stable and high reliability products.

CAP	TOL
≤5pF	A±0.1pF B±0.5pF
≥5F<10pF	C±0.25pF D±0.5pF
≥10F	J±5% K±10% M±20% Z+80-20%



RATED W. V	TEMP.CHARACTERISTICS & CAPACITANCE RANGE				DIMENSION			
	SL	Y5P(B)	Y5U(E)	Y5V(F)	D	P	T	d
4KV				102	07	7.5~10	5	0.6 0.8
		221~471	102	222	09			
		561~681	222	472	11			
		102	332~472	103	14			
6.3KV		221~471		102	08	7.5~10	6	0.6 0.8
		561~681	102	222	10			
		102	222	472	13			
		152~222	332~472	103	16			
		332~472	103		21			
8KV		221~471	102	102	10	7.5~10	7	0.6 0.8
		681~102	222	222	13			
		152~222	472	472	16			
				103	22			
10KV		101~221		102	09	10~12	8	0.8
		471~561		152	10			
		681~102	102	222	13			
		152	332	472	16			
		222	682		19			
		332		103	22			
15KV		101~221		102	09	10~12	9	0.8
		471~561	102	222	13			

		102	222	472	16			
20KV	10~30	201~271		102	10	10	8	0.6
		331~511	102	222	14	10	8	0.8
		102	222	332	18	12.5	9	0.8
			472	103	24	12.5	9	0.8
30KV		102	472	103	26	15	12	1.5
40KV		102	332		30	15	20	1.5
50KV		102	472		36	15	22	1.5